Revision & Date: S60331R

SCOPLEANER-7 ™

Fiber Optic Cleaner Combined Scope

Special Features

- · Just One Step for "Scopping Cleaning Scopping"
- Within 3 seconds for "Scopping Cleaning Scopping"
- · One handed operation
- Wide 5.6" TFT LCD Monitor
- · Low Price but good capacity
- · Foldable Monitor and adjustable Angle
- Low Noise of DC12V Motor Pump by AC 110/220V
- · Save Data on PC by USB device
- · Brightness & Contrast adjustable
- · Easy and usage by setup
- · Anti-slip Grip design and Easy Focus
- · Complied with RoHS
- · CE/FCC approved



Specifications

Brand Name		Scopleaner-7
Cleaning Method		Solvent Non-Contact Cleaning System
		Use 3M Solvent (P/N:HFE-72DE) or Puretecs puresolve 7200
		Non-Flammable, Zero Ozone Depletion
Driving Type		Motor Pump, DC 12V
Cleaning Time		Within 3 sec for "Scopping-Cleaning-Scopping"
Cleaning Tip		LC/PC (standard)
Power Supply		12V Power Supply by AC 100~240V Adaptor
USB Device with Software (option)		Pass/Fail Analysis to IEC 61300-3-35
LCD with Magnification		5.6" TFT LCD, 260X
Dimension	Handset (with Tip)	245mm (L) x 24mm (T)
	Main Body (when Monitor folded)	200mm (W) x 210mm (L) x 170mm (H)
Weight		8kgs

Standard Package

P/N: Scopleaner-7

- 1 Main Body with LCD Monitor
- 1 Handset
- 1 LC/PC Female side Cleaning Tip
- 1 Rubber Cap
- 1 AC Power Cord
- 1 PushCleaner-1.25
- 1 Funnel
- 1 Manual
- 1 Transport Bag

[Option] USB Device with Pass/Fail Analysis Software is available optionally.



Manufacturer : TheFibers Inc.

A-1109 Keumkang Penterium IT Tower, 282 Hagui-ro, Anyang-City, Korea Tel: +82-31-381-6108 Fax: +82-31-381-6109 sales@thefibers.com